

1533R Multi-Conductor - Category 5e Nonbonded-Pair Cable



For more Information
please call

1-800-Belden1



General Description:

CAT5e (100MHz), 4-Pair, F/UTP-Foil shielded, Riser-CMR, Premise Horizontal Cable, 24 AWG solid bare copper conductors, polyolefin insulation, overall Beldfoil® shield,PVC jacket, RJ-45 compatible

Usage (Overall)

Suitable Applications: Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422, Noisy Environments, 100MHz Category 5e

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4 | 24 | Solid | BC - Bare Copper |

Total Number of Conductors: 8

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| PO - Polyolefin |

Outer Shield

Outer Shield Material:

| Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|-------------------------|------|------------------------------|--------------|
| Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 24 | 7x32 | TC - Tinned Copper |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Outer Jacket Diameter:

| Nom. Dia. (in.) |
|-----------------|
| 0.260 |

Pair

Pair Color Code Chart:

| Number | Color |
|--------|------------------------------|
| 1 | White/Blue Stripe & Blue |
| 2 | White/Orange Stripe & Orange |
| 3 | White/Green Stripe & Green |
| 4 | White/Brown Stripe & Brown |

Mechanical Characteristics (Overall)

Operating Temperature Range: -20°C To +75°C

Bulk Cable Weight: 30 lbs/1000 ft.

1533R Multi-Conductor - Category 5e Nonbonded-Pair Cable

| | |
|-----------------------------------|-----------|
| Max. Recommended Pulling Tension: | 25 lbs. |
| Min. Bend Radius/Minor Axis: | 1.100 in. |
| Min. Bend/Installation: | 2.600 in. |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|---------------------------------------|--|
| NEC/(UL) Specification: | CMR, UL444 |
| CEC/C(UL) Specification: | CMR |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| Other Standards: | 11801 Category 5 |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Telecommunications Standards: | 568-B.2 Category 5e |
| Other Specification: | NEMA WC-63.1 Category 5e, UL Verified to Category 5e |

Flame Test

| | |
|-----------------|--------------|
| UL Flame Test: | UL1666 Riser |
| CSA Flame Test: | FT4 |

Plenum/Non-Plenum

| | |
|----------------|-------|
| Plenum (Y/N): | No |
| Plenum Number: | 1533P |

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

| | |
|---------------------|----|
| Capacitance (pF/ft) | 15 |
|---------------------|----|

| | |
|---|-----|
| Maximum Capacitance Unbalance (pF/100 m): | 330 |
|---|-----|

Nominal Velocity of Propagation:

| | |
|--------|----|
| VP (%) | 70 |
|--------|----|

Maximum Delay:

| | |
|------------------|--------------|
| Delay (ns/100 m) | 538 @ 100MHz |
|------------------|--------------|

Max. Delay Skew:

| | |
|-----------------------|----|
| Delay Skew (ns/100 m) | 45 |
|-----------------------|----|

Maximum Conductor DC Resistance:

| | |
|------------------------|------|
| DCR @ 20°C (Ohm/100 m) | 9.38 |
|------------------------|------|

Max. Operating Voltage - UL:

| | |
|---------|-----------|
| Voltage | 300 V RMS |
|---------|-----------|

Maximum DCR Unbalanced:

1533R Multi-Conductor - Category 5e Nonbonded-Pair Cable

DCR Unbalance @ 20°C (%)

3

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) | Min. SRL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|---------------|
| 1 | 2.0 | 65.3 | 62.3 | 60.3 | 60.3 | 20.0 | 23.0 |
| 4 | 4.1 | 56.3 | 53.3 | 49.2 | 49.2 | 23.0 | 23.0 |
| 8 | 5.8 | 51.8 | 48.8 | 43.0 | 43.0 | 24.5 | 24.5 |
| 10 | 6.5 | 50.3 | 47.3 | 40.8 | 40.8 | 25.0 | 25.0 |
| 16 | 8.2 | 47.3 | 44.3 | 36.0 | 36.0 | 25.0 | 25.0 |
| 20 | 9.3 | 45.8 | 42.8 | 33.5 | 33.5 | 25.0 | 25.0 |
| 25 | 10.4 | 44.3 | 41.3 | 30.9 | 30.9 | 24.3 | 24.3 |
| 31.25 | 11.7 | 42.9 | 39.9 | 28.2 | 28.2 | 23.6 | 23.6 |
| 62.5 | 17.0 | 38.4 | 35.4 | 18.4 | 18.4 | 21.5 | 21.5 |
| 100 | 22.0 | 35.3 | 32.3 | 10.3 | 10.3 | 20.1 | 20.1 |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. ELFEXT (dB) | Min. PSELFEXT (dB) |
|-------------|------------------------------|------------------|------------------|--------------------|
| 1 | 100 ± 15 | 100 ± 15 | 63.8 | 60.8 |
| 4 | 100 ± 15 | 100 ± 15 | 51.7 | 48.7 |
| 8 | 100 ± 15 | 100 ± 15 | 45.7 | 42.7 |
| 10 | 100 ± 15 | 100 ± 15 | 43.8 | 40.8 |
| 16 | 100 ± 15 | 100 ± 15 | 39.7 | 36.7 |
| 20 | 100 ± 15 | 100 ± 15 | 37.7 | 34.7 |
| 25 | 100 ± 15 | 100 ± 15 | 35.8 | 32.8 |
| 31.25 | 100 ± 15 | 100 ± 15 | 33.9 | 30.9 |
| 62.5 | 100 ± 15 | 100 ± 15 | 27.8 | 24.8 |
| 100 | 100 ± 15 | 100 ± 15 | 23.8 | 20.8 |

Notes (Overall)

Notes: Shield is bonded to jacket inner wall for electrical stability. RJ-45 Compatible. Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|----------------|----------|-------------|-------------|-------|--------------------------|
| 1533R F2VA1000 | 1,000 FT | 35.000 LB | GRAY, DEC | | CAT5E 4PR F/UTP CMR RIB |
| 1533R F2V1000 | 1,000 FT | 34.000 LB | GRAY, DEC | C | CAT5E 4PR F/UTP CMR REEL |
| 1533R F2V1640 | 1,640 FT | 57.400 LB | GRAY, DEC | C | CAT5E 4PR F/UTP CMR REEL |
| 1533R 002A1000 | 1,000 FT | 35.000 LB | RED | C | CAT5E 4PR F/UTP CMR RIB |
| 1533R 0021000 | 1,000 FT | 34.000 LB | RED | C | CAT5E 4PR F/UTP CMR REEL |
| 1533R 003A1000 | 1,000 FT | 35.000 LB | ORANGE | C | CAT5E 4PR F/UTP CMR RIB |
| 1533R 0031000 | 1,000 FT | 34.000 LB | ORANGE | C | CAT5E 4PR F/UTP CMR REEL |
| 1533R 004A1000 | 1,000 FT | 35.000 LB | YELLOW | C | CAT5E 4PR F/UTP CMR RIB |
| 1533R 0041000 | 1,000 FT | 34.000 LB | YELLOW | C | CAT5E 4PR F/UTP CMR REEL |
| 1533R 005A1000 | 1,000 FT | 35.000 LB | GREEN, DARK | C | CAT5E 4PR F/UTP CMR RIB |
| 1533R 0051000 | 1,000 FT | 34.000 LB | GREEN, DARK | C | CAT5E 4PR F/UTP CMR REEL |
| 1533R 006A1000 | 1,000 FT | 35.000 LB | BLUE, LIGHT | | CAT5E 4PR F/UTP CMR RIB |
| 1533R 0061000 | 1,000 FT | 34.000 LB | BLUE, LIGHT | C | CAT5E 4PR F/UTP CMR REEL |
| 1533R 010A1000 | 1,000 FT | 35.000 LB | BLACK | | CAT5E 4PR F/UTP CMR RIB |
| 1533R 0101000 | 1,000 FT | 34.000 LB | BLACK | C | CAT5E 4PR F/UTP CMR REEL |

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 08-06-2013

© 2013 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications

1533R Multi-Conductor - Category 5e Nonbonded-Pair Cable

described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.